



Felt Wall-Slat Panel System



Made using two layers of premium recycled felt, our Wall-Slat System provides the simple textures and color variations that make a room come alive. The 12mm slats are available in four colors and the 22.75" wide sections can be placed end to end to cover large areas. This system tested as a 0.65 NRC!

Construction & Installation

Peel n Stick

Leave the hardware, screws, drills, and whatever else in the drawer! Peel n Stick is a double-sided press-on adhesive specifically designed for Mode products! To adhere, simply make a level line guide, press-on planks & go!

Colors


Slats



Backing Board



Absorption Coefficient vs. Freq (Hz)



Freq (Hz) Absorption Coefficient

160	0.21
250	0.20
500	0.40
800	0.70
1000	0.90
2000	1.10
3150	1.04
NRC	0.65

The Noise Reduction Coefficient (NRC) is calculated as the arithmetic average of the absorption coefficients in the shaded bands only (250, 500, 1250 & 2000 Hz).

ASTM C 423-17: Type A Mounting – Test specimen laid directly against the test surface to simulate a typical wall installation.

Specifications

Product Name	Felt Wall-Slat Panel System
Lead Times	Fast Ship: 4 weeks Standard: 10 weeks
Content	100% Polyester (PET) with a minimum of 60% recycled content
Thickness	9 & 12mm
Width	22.75"
Height	95.5"
Max Depth	21mm
Weight	11 lbs per sq ft
Edge Options	Exposed felt
Sound Performance	ASTM C423-17: NRC = 0.65. Adding a 1–2" air gap behind panel can add 15-20% better NRC performance.
Fire Performance	Class A (ASTM 84)
Variations	Mode Felt uses an industry standard felting process. Slight and consistent variations in color and "heathering" should be expected when using this sustainable material. Slight imperfections are within normal manufacturing tolerance and not visible in standard installations.
Environmental	Low VOC emissions, formaldehyde and phenol-free. Red List free.
Maintenance	Vacuum to remove any loose dirt or dust then use a soft or plastic bristle brush to loosen. Avoid excess pressure. Compressed air can also be used in difficult or large installations. If stains are present, saturate a lint-free cloth with a mild detergent or soap and water solution.
Warranty	10 years
Unit of Sale	Per section, minimum order quantity: 2